

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 1/05	A1	(11) International Publication Number: WO 95/34156 (43) International Publication Date: 14 December 1995 (14.12.95)
(21) International Application Number: PCT/US95/06614 (22) International Filing Date: 24 May 1995 (24.05.95) (30) Priority Data: 08/254,379 6 June 1994 (06.06.94) US (71) Applicant: THE CREATIVE SOLUTIONS COMPANY, INC. [US/US]; 14853 Grantley Drive, Chesterfield, MO 63017 (US). (72) Inventor: GUENTHER, Donald, E.; 14853 Grantley Drive, Chesterfield, MO 63017 (US). (74) Agents: GODAR, Michael, E. et al.; Senniger, Powers, Leavitt & Roedel, 16th floor, One Metropolitan Square, St. Louis, MO 63102 (US).		(81) Designated States: BR, CA, JP, KR, MX, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: CELLULAR TELEPHONE HEADSET**(57) Abstract**

A headset (1) for use with a cellular phone (30) comprises an acoustical earpiece assembly (11) adapted for the acoustical transmission of sound to the ear (13), a device for mounting the earpiece assembly (11) on the head in a position adjacent an ear (11) of a person wearing the headset (1), and a flexible acoustical receiving tube (15) having an upper end (17) connected to the earpiece assembly (11) and a lower end (19) attached to an acoustical receiving cup (21). The headset (1) also includes a device for releasably attaching the acoustical receiving cup (21) to a telephone speaker (9) for receiving sound emitting from the speaker (9). The earpiece assembly (11) has a transmitter mechanism for picking up sound made by the person wearing the headset (1), and for transmitting such sounds from the transmitter to the telephone (3).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

CELLULAR TELEPHONE HEADSETBackground of the Invention

This invention relates generally to the cellular telephone industry, and more particularly to a headset which facilitates the use of a cellular telephone.

Conventional cellular telephones, which have become extremely popular, are cumbersome to use, especially by the driver of a vehicle. If the telephone is picked up and held by hand, the driver loses the use of that hand for driving or other purposes. In an effort to free up both hands, drivers often attempt to hold the phone between the shoulder and neck, which is not only uncomfortable but also dangerous because it restricts the full range of head movement and peripheral vision necessary for safe driving.

Some cellular telephones are operable in a "hands-free" mode, where the user of the phone speaks into a microphone (usually mounted on the sun visor on the driver's side) connected to the mechanism inside the transmitter of the telephone. While this arrangement dispenses with the need to hold the telephone, the microphone tends to pick up extraneous sounds, such as wind, engine noise, radio and traffic. This can severely impair the quality and clarity of speech transmitted by the telephone.

There is a need, therefore, for a cellular telephone system which avoids these problems.

Summary of the Invention

Among the several objects of this invention may be noted the provision of a headset which facilitates the use of a cellular phone; the provision of such a headset which allows the user of the phone to converse without holding the

phone; the provision of such a headset which provides for the clear transmission of speech without interference from outside environmental noise; the provision of such a headset which is lightweight, comfortable to wear and aesthetically pleasing; the provision of such a headset which does not interfere with the wearer's peripheral vision; the provision such a headset which, in one embodiment of the invention, is fabricated using no electronic components for more economical manufacture; and the provision of such a headset which is easy to connect to a phone and convenient to use.

Briefly, a headset of this invention is for use with a cellular telephone having a telephone receiver and a telephone transmitter. The headset comprises an acoustical earpiece assembly adapted for the acoustical transmission of sound to the ear, means for mounting the earpiece assembly on the head in a position adjacent an ear of a person wearing the headset, a flexible acoustical receiving tube having an upper end connected to the earpiece assembly and a lower end attached to an acoustical receiving cup. The headset comprises a device for releasably attaching the acoustical receiving cup to a telephone in a position where the mouth of the cup is disposed closely adjacent the telephone speaker for receiving sound emitting from the speaker. The acoustical cup is adapted for the acoustical transmission of sound to the earpiece assembly via the acoustical receiving tube. The earpiece assembly has a transmitter means for picking up sounds made by a person wearing the headset, and for transmitting such sounds to the transmitter of the telephone.

In a second aspect of this invention, the headset comprises an acoustical earpiece assembly, means for mounting the earpiece assembly on the head, a flexible acoustical receiving tube, an acoustical receiver, a device

for releasably attaching the acoustical receiver to a telephone and a transmitter means comprising a microphone support extending forward from the earpiece assembly at one side of the head of a person wearing the headset to a position generally adjacent the mouth of the person, a microphone at the forward end of the microphone support for picking up sounds from the person, and electrical conductor means for connecting the microphone to a microphone plug associated with the transmitter of the telephone.

10 In a third aspect of this invention, the headset comprises an acoustical earpiece assembly, means for mounting the earpiece assembly on the head, a flexible acoustical receiving tube, an acoustical receiver, a device for releasably attaching the acoustical receiver to a telephone and a transmitter means comprising a relatively short acoustical pick-up tube extending forward from a earpiece housing at one side of the head of a person wearing the headset, and a flexible acoustical transmitting tube having an upper end connected to the earpiece housing and communicating acoustically with said pick-up tube, and a lower end adapted to communicate acoustically with the transmitter of the telephone. The acoustical pick-up and transmitting tube are adapted to acoustically transmit sounds made by a person wearing the headset to the transmitter of the telephone. The housing is pivotable relative to the hanger about an axis extending in generally side-to-side direction with respect to the head of a person wearing the headset to enable adjustment of the position of the acoustical pick-up tube relative to the head of the person.

Other objects and features will be in part apparent and in part pointed out hereinafter.

Brief Description of the Drawings

Fig. 1 shows a headset of this invention in use with a cellular telephone;

Fig. 2 is a side view of an earpiece assembly of the headset of Fig. 1 mounted on the ear by means of a hanger;

Fig. 3 is a front view of the earpiece assembly of Fig. 2;

Fig. 4 is a view of a cellular telephone attached to the headset, showing an acoustical receiving cup secured over the speaker of the telephone;

Fig. 5 is a cross-sectional view of the earpiece assembly of Fig. 2;

Fig. 6 is an enlarged view of the earpiece assembly of Fig. 2, parts being broken away to illustrate details;

Fig. 7 is an enlarged sectional view of the acoustical receiving cup and receiving tube of Fig. 4;

Fig. 8 is an enlarged portion of Fig. 4 illustrating how the receiving cup is secured in place on the telephone by an elastic band;

Fig. 9 is an enlarged portion of Fig. 4 illustrating how the receiving cup is secured in place on the telephone with a Velcro® strap;

Fig. 10 is an enlarged view of a ratchet surface on the housing of the earpiece assembly of Fig. 2;

Fig. 11 is an enlarged view of the hanger of Fig. 2 showing a ratchet surface adapted to mate with the ratchet surface on the housing;

Fig. 12 is an enlarged sectional view along lines 12--12 of Fig. 5, parts being removed to show certain details;

Fig. 13 is a side view of an alternative headset design using no electronic components; and

Fig. 14 is a view showing an acoustical receiving cup and sound cup of the headset of Fig. 13 secured over the speaker and transmitter, respectively, of a cellular telephone.

Corresponding parts are designated by corresponding reference characters throughout the several views of the drawings.

10 Detailed Description of the Preferred Embodiment

Referring now to the drawings, and first to Fig. 1, there is generally indicated at 1 a headset of this invention for use with a cellular telephone, generally designated 3. The telephone may be of any type having a receiver 5 and a transmitter 7. The telephone 3 can be used in regular fashion by holding the phone in one hand, or in a "hands-free" mode in which the telephone remains in its cradle 8, as shown. In the "hands-free" mode, the caller's voice is transmitted via a speaker 9 (Fig. 8) on the back of telephone. The headset 1 illustrated in the drawings is used when the telephone is operated in its "hands-free" mode.

The headset 1 comprises an acoustical earpiece assembly, generally indicated at 11, adapted for the acoustical transmission of sound to the ear 13 (Fig. 2), means comprising a hanger generally designated 14 for mounting the earpiece assembly on the head in a position adjacent an ear of the person wearing the headset, and a flexible acoustical receiving tube 15 having an upper end 17 connected to the earpiece assembly and a lower end 19 (Figs. 3 and 4). An acoustical receiving cup 21 at the lower end 19 of the acoustical receiving tube is releasably attached

by suitable means to the telephone 3 in a position closely adjacent to the telephone speaker 9 (Fig. 8) for receiving sound emitting from the speaker, the sound thus emitted being transmitted to the earpiece assembly 11 via the acoustical receiving tube 15 (Fig. 4). The headset 1 also includes transmitter means, generally designated 23 (Fig. 1), attached to the earpiece assembly 11 for picking up sounds made by a person wearing the headset, and for transmitting such sounds to the transmitter 7 of the telephone.

More specifically, the earpiece assembly 11 comprises a housing, generally indicated at 25, and an ear insert 27 attached to the housing adapted to be positioned in or near the outer opening of the ear 13 when the earpiece assembly 11 is mounted on the head. As shown in Fig. 5, the housing 25 is of two-part construction, comprising a first inboard part 29 disposed adjacent the ear, and a second outboard part 31 disposed away from the ear. The two parts are preferably molded from a suitable plastic (e.g., ABS plastic) and formed to snap fasten to one another so that they may be assembled without the use of mechanical fasteners. When assembled, the two housing parts 29, 31 form a chamber 33. A tubular post 35 integrally formed (molded) with the inboard part 29 of the housing 25 projects laterally from the housing toward the ear of the user. The inside of the post 35 defines a passage 36 which opens into the chamber 33 of the housing 25. The post 35 comprises a plurality of separate resilient spring fingers 37 extending the length of the post, each finger having a latch 41 at its outer end projecting generally radially outwardly with respect to the passage 36 through the post. The latches 41 on these fingers 37 are received in an annular groove 51 formed in the ear insert 27 to snap fasten the insert to the

housing 25 in a position where the insert is adapted to be positioned in or near the outer opening of the ear when the earpiece assembly 11 is mounted on the head.

The ear insert 27 has a relatively large annular base 53 concentric with the post 35 on the housing 25, and a tubular stem 55 projecting from the base axially with respect to the post. The ear insert 27 is preferably of one-piece molded plastic construction and formed to snap fasten on post 35 of the housing 25 and to lock into place by means of the resilient spring fingers 37 and latches 41 described above. The annular base 53 of the ear insert 27 supports a foam cushion cover 57 which is provided for user comfort. The stem 55 of the ear insert 27 is formed with a plurality of rings 59 which function to properly position and hold the insert in the opening of the ear, and to deaden the transmission of environmental sound to the ear. The tubular stem 55 forms a passageway 61 that communicates with the passage 36 through the post 35 and the acoustic chamber 33 of the housing 25 (see Fig. 5). The ear insert 27 should be of a relatively soft flexible plastic (e.g., silicone, PVC) to avoid risk of injury to the ear.

As shown in Figs. 2, 5 and 11 the hanger 14 for mounting the earpiece assembly 11 on the head comprises an arched section 73 configured to fit behind the ear of a person wearing the headset, and a thin flat annular hub 77 mounted on the post 35 of the housing 25 in a position sandwiched between the inboard part 29 of the housing and the base 53 of the ear insert 27. The earpiece housing 25 is pivotable relative to the hanger 14 about an axis A extending in generally side-to-side direction with respect to the head of a person wearing the headset (Fig. 5). The reason for this pivotal movement will be discussed later.

As shown best in Fig. 5, the upper end 17 of the acoustical receiving tube 15 extends through an opening 79 in the housing 25 of the earpiece assembly 11, through the chamber 33 in the housing, and through the passage 36 in the post 35 so that the end 17 of the tube is substantially coaxial with the passage 61 through the stem 55 of the ear insert 27. The end of the tube abuts against an internal annular shoulder 85 in the stem 55 having a width approximately the same as the wall thickness of the receiving tube 15 so that the passages through the receiving tube and stem 55 combine to form a continuous acoustical passageway of substantially uniform diameter. An annular rib 87 adjacent the opening 79 in the housing applies a compressive force to the receiving tube 15 to provide strain relief to assist in holding the tube in place.

The acoustical receiving cup 21 attached to the lower end of the receiving tube 15 is shown in Fig. 7. The cup 21 has a generally conical body 89 having a relatively wide, open mouth 91 adapted to be attached to the telephone 3 in a position wherein the mouth of the cup is closely adjacent the telephone speaker 9 (Fig. 8) for receiving sound emitting from the speaker. The cup 21 is formed with an integral sleeve 93 projecting laterally from the cup body 89 at its upper end. This sleeve is sized to receive the lower end 19 of the acoustical receiving tube 15, the fit being a close friction fit sufficient to hold the tube tightly within the sleeve 93. The end of the tube 15 is bevelled as shown in Fig. 7 to minimize interference with the transmission of sound from the speaker 9 of the telephone to the earpiece assembly 11.

The receiving cup 21 may be attached to the telephone in any number of ways. One such way, illustrated in Fig. 9, is by the use of a strap 97 attached to the cup

and having interengageable hook and loop type (Velcro®) fasteners 98 affixed thereto at opposite ends of the strap. The strap may be attached to the cup 21 by means of a boss 99 on the cup inserted through an opening in the strap.

- 5 Alternatively, one or more elastic bands 102 may be used, as shown in Fig. 8. It will be understood that other means for removably attaching the cup 21 to the telephone are also suitable.

The transmitter means 23 shown in Fig. 2 comprises
10 a J-shaped arm 100 of substantially rigid material attached to the housing 25 of the earpiece assembly 11. The arm has a straight shank portion 101, the rearward end of which has a slip fit over a connector in the form of a sleeve 103 (Fig. 5) rotatably mounted in an opening 105 in the housing
15 25 of the earpiece assembly 11. As shown in Fig. 5, the sleeve 103 has a circular radial flange 106 at its rearward (upper) end received in a circular groove 108 formed in the housing, the sleeve thus being held rotatably captive in the housing 25. The shank portion 101 of the arm extends
20 forward and downward from the housing 25 at one side of the head of a person wearing the headset 1. The J-shaped arm also has a curved end portion 109 which curves laterally inwardly from the shank portion 101. The configuration of the arm 100 is such that the tip of its curved end portion
25 109 is positioned adjacent the mouth of a person wearing the headset.

Transmitter means 23 also includes a miniature microphone 111 supported by the J-shaped arm 100 at the tip of its forward end. This microphone 111 may be of
30 conventional design, one such microphone being commercially available from Radio Shack under the trade designation #33-3003. A funnel-shaped sound cone 114 mounted at the forward end of the arm surrounds the microphone 111 and functions to

gather sounds directed generally in the direction of the microphone for pick-up by the microphone. A microphone wire 115 extends from the microphone 111 rearwardly through the tubular arm 100, through the sleeve 103, and into the chamber 33 of the housing 25 (Figs. 5 and 6). From there, the wire 115 passes through a flexible tube 116 running alongside the acoustical receiving tube 15 and is connected at its lower end by means of a suitable connector 118 (preferably a quick-connect, quick-disconnect connector) adapted to mate with connector 117 attached to a microphone mechanism or system 140 associated with the transmitter 7 of the telephone, as will be described later. To facilitate use of the device, and to improve appearance, the receiving tube 15 and the tube 116 housing the earpiece housing 111 be integrally joined side-by-side along much of their lengths, i.e., from a location inside the telephone 25 to a location generally adjacent the earpiece housing 111 relative to the head and mouth of the wearer of the headset 1, the J-shaped arm 100 is adjustable in two ways. First, the arm is rotatable on the longitudinal axis of its shank 101 to move the outer part 109 of the arm carrying the microphone 111 up and down relative to the mouth of the wearer. This is accomplished simply by rotating the arm 100 and the sleeve 105 on which it is mounted relative to the housing 25 (the fit of the sleeve in the housing is sufficiently tight that the arm remains in its adjusted position until forcibly moved to a different position). Second, the arm 100 and the housing 25 of the earpiece assembly 11 are conjointly rotatable on axis A relative to the ear hanger 14 (i.e., the shank 101 of the arm pivots in a generally vertical plane extending in front-to-rear

direction with respect to the wearer) for adjusting the position of the arm to suit the wearer.

Indicated generally at 121 (Fig. 12) is a detent mechanism for maintaining the housing 25 and J-arm 100 in a selected position of angular adjustment. This mechanism 121 comprises a series of alternating ratchet grooves 123 and teeth 125 arranged around the central opening in the annular hub 77 of the hanger 14 on the outwardly facing surface of the hub, and a complementary series of alternating ratchet grooves 127 and teeth 129 on the opposing surface of the inboard part 29 of the housing 25. The grooves and teeth extend radially with respect to axis A. The arrangement is such that the teeth 125 on the hub are receivable in the grooves 127 on the housing, and the teeth 129 on the housing 25 are receivable in the grooves 123 on the hub (see Fig. 12) to lock the housing in a selected angular position relative to the hanger 14 according to the desired angular position of the J-arm 100 (see Fig. 12). As shown in Fig. 5, a resilient spring element 131 formed on the base 53 of the ear insert 27 resiliently urges the housing 25 and hanger hub 77 toward one another to maintain the ratchet grooves and teeth on the opposing surfaces in interengagement. The force exerted by this spring element is sufficiently weak that it can be easily overcome, if desired, to rotate the housing 25 relative to the hanger 14 to readjust the position of the J-arm 100.

To use the headset 1 of Fig. 1, the microphone wiring 115 is simply connected to the transmitter 7 of the telephone or equipment associated with transmitter. If the telephone has a conventional "hands-free" speaker feature, this simply involves disconnecting connector 119 attached to the wiring 135 of the standard hands-free microphone 137 (typically mounted on the driver's side visor) and

connecting the microphone wiring 115 of the headset of this invention by means of connector 118 to preexisting connector 117 attached to the wiring 140 leading to the transmitter 7 of the telephone. Other types of connector arrangements can be used to mate with different configurations of systems associated with the transmitter 7 of a cellular telephone. In the future, cellular phones may have direct inputs to accommodate the wiring of this invention.

Figs. 13 and 14 illustrate an alternative embodiment of the headset of the invention, generally designated 201. This embodiment is similar to the version described above, except that it includes no electronic components. That is, the microphone and associated wiring are eliminated. Sound from the wearer of the headset is transmitted acoustically through a J-shaped pick-up tube 200 having a funnel-shaped sound cone 214 at its forward end for gathering the sound and directing it into the tube. The rearward end of the tube is in acoustic communication with the chamber 233 in the housing 225, and the upper end of an acoustic transmitting tube 216 corresponding to the tube 116 of the headset of the first embodiment is in acoustic communication with the chamber 233 in the housing. The arrangement is such that sound is transmitted through the rearward end of the pick-up tube, through the acoustic chamber 233, and then down through the acoustic transmitting tube 216 to a sound cup 205 attached to the transmitting end 5 of the telephone 3, as shown in Fig. 14. This sound cup 205 is identical to the sound cup 21 described earlier and may be removably attached to the telephone in identical fashion (e.g., by a Velcro® strap 98 or an elastic band 102). The other components of the headset 201 are identical to those described in the embodiment of Figs. 1-12, and such

components are identified by the same reference numbers in Figs. 13 and 14 where appropriate.

In view of the above, it will be seen that the several objects of the invention are achieved and other
5 advantageous results attained.

As various changes could be made in the above constructions without departing from the scope of the invention, it is intended that all matter contained in the above description or shown in the accompanying drawings
10 shall be interpreted as illustrative and not in a limiting sense.

WHAT IS CLAIMED IS:

1. A headset for a cellular telephone, said cellular telephone having a speaker and a transmitter, said headset comprising:

an acoustical earpiece assembly adapted for the
5 acoustical transmission of sound to the ear,

means for mounting the earpiece assembly on the head in a position adjacent an ear of a person wearing the headset,

a flexible acoustical receiving tube having an
10 upper end connected to said earpiece assembly, and a lower end,

an acoustical receiving cup attached to the lower end of the acoustical receiving tube, said acoustical receiving cup having a relatively wide, open mouth,

15 a device for releasably attaching the acoustical receiving cup to said telephone in a position where the mouth of the cup is disposed closely adjacent the telephone speaker for receiving sound emitting from the speaker, said acoustical cup being adapted for the acoustical transmission
20 of said sound to said earpiece assembly via said acoustical receiving tube, and

transmitter means attached to the earpiece assembly for picking up sounds made by a person wearing the headset, and for transmitting such sounds to the transmitter
25 of the telephone.

2. A headset as set forth in claim 1 wherein said device for releasably attaching the acoustical receiving cup to the telephone comprises Velcro strap means.

3. A headset as set forth in claim 1 wherein said device for releasably attaching the acoustical receiving cup to the telephone comprises elastic band means.

4. A headset as set forth in claim 1 wherein said earpiece assembly comprises a housing and an ear insert attached to the housing adapted to be positioned in or near the outer opening of the ear when the earpiece assembly is
5 mounted on the head, the upper end of said acoustical receiving tube being connected to the housing and communicating acoustically with the ear insert for transmission of sound to the ear.

5. A headset as set forth in claim 4 further comprising a snap fastener for snap fastening said ear insert to the housing.

6. A headset as set forth in claim 4 wherein said transmitter means comprises a generally J-shaped pick-up tube having a shank portion extending forward from the housing at one end of the head of a person wearing the
5 headset, and a forward end portion extending generally laterally with respect to the shank portion, the shank portion of the pick-up tube having a connection with the housing permitting rotation of the pick-up tube about a longitudinal axis of the shank portion thereby to permit
10 adjustment of the position of the forward end portion of the pick-up tube relative to the mouth of a person wearing the headset.

7. A headset as set forth in claim 6 wherein said earpiece assembly further comprising a connector connecting the shank portion of the pick-up tube to the housing, said housing comprising two separate parts adapted to snap-fasten
5 together to form a unitary housing, said housing being configured to hold said connector rotatably captive with respect to the housing when the two parts of the housing are snap fastened together.

8. A headset as set forth in claim 4 wherein said means for mounting the earpiece assembly on the head comprises a hanger on the housing engageable with the ear for supporting the earpiece assembly on the ear.

9. A headset as set forth in claim 1 wherein said transmitter means comprises a first part attached to said earpiece assembly configured to assume a position adjacent the mouth when the headset is worn for picking up said
5 sounds made by a person wearing the headset, and a second part attached to said earpiece assembly for transmitting said sounds to said telephone transmitter.

10. A headset as set forth in claim 9 wherein the first part of the transmitter means comprises a relatively short acoustical pick-up tube extending forward from the earpiece assembly at one side of the head of a person
5 wearing the headset, and wherein the second part of the transmitter means comprises a flexible acoustical transmitting tube having an upper end acoustically communicating with said pick-up tube and a lower end adapted for releasable attachment to the telephone adjacent the
10 transmitter of the telephone, said acoustical pick-up and

transmitting tubes being adapted to acoustically transmit said sounds made by a person wearing the headset to the transmitter of the telephone.

11. A headset as set forth in claim 10 wherein said flexible transmitting and receiving tubes are integrally connected in side-by-side relation.

12. A headset as set forth in claim 10 wherein said earpiece assembly comprises a housing defining an acoustical chamber, and an ear insert attached to the housing adapted to be positioned in or near the outer
5 opening of the ear when the earpiece assembly is mounted on the head, the upper end of said acoustical receiving tube being connected to the housing and communicating acoustically with the ear insert for transmission of sound to the ear, said pick-up tube having a rearward end
10 communicating acoustically with said acoustical chamber, and the upper end of the acoustical receiving tube communicating acoustically with the acoustical chamber.

13. A headset as set forth in claim 12 further comprising a snap fastener for snap fastening said ear insert to the housing.

14. A headset as set forth in claim 12 wherein said means for mounting the earpiece assembly on the head comprises a hanger on the earpiece housing engageable with the ear for supporting the earpiece assembly on the ear.

15. A headset as set forth in claim 14 wherein said earpiece housing is pivotable relative to said hanger about an axis extending in generally side-to-side direction with respect to the head of a person wearing the headset to enable adjustment of the position of the forward end of the pick-up tube relative to the mouth of said person.

16. A headset as set forth in claim 15 further comprising a detent mechanism for maintaining the earpiece housing in a selected position of angular adjustment.

17. A headset as set forth in claim 10 further comprising an acoustical transmitting cup attached to the lower end of the acoustical transmitting tube for directing sound emitting from the transmitting tube to the transmitter of the telephone, and a device for releasably attaching the acoustical transmitting cup to the telephone adjacent to the transmitter of the telephone.

18. A headset as set forth in claim 17 wherein said acoustical transmitting cup has a wide, open mouth and is adapted to be attached to the telephone in a position wherein the mouth of the cup is closely adjacent the transmitter of the telephone.

19. A headset as set forth in claim 18 wherein said device for releasably attaching the acoustical transmitting cup to the telephone comprises Velcro® strap means.

20. A headset as set forth in claim 19 wherein said device for releasably attaching the acoustical transmitting cup to the telephone comprises elastic band means.

21. A headset as set forth in claim 5 wherein the first part of said transmitter means comprises a microphone support extending forward from the earpiece assembly at one side of the head of a person wearing the headset to a
5 position generally adjacent the mouth of the person, and a microphone at the forward end of the support, said second part of the transmitter means comprising electrical conductor means for connecting the microphone to a microphone mechanism associated with the transmitter of the
10 telephone.

22. A headset as set forth in claim 21 further comprising a quick-connect, quick-disconnect coupling for releasably coupling said electrical conductor means to said microphone mechanism associated with the transmitter of the
5 telephone.

23. A headset for a cellular telephone, said cellular telephone having a speaker and a transmitter, said headset comprising:

an acoustical earpiece assembly adapted for the
5 acoustical transmission of sound to the ear,

means for mounting the earpiece assembly on the head in a position adjacent an ear of a person wearing the headset,

a flexible acoustical receiving tube having an
10 upper end connected to said earpiece assembly, and a lower end,

an acoustical receiver attached to the lower end of the acoustical receiving tube,

15 a device for releasably attaching the acoustical receiver to said telephone in a position where the receiver is disposed for receiving sound emitting from the speaker of the telephone, said acoustical receiver being adapted for the acoustical transmission of said sound to said earpiece assembly via said acoustical receiving tube, and

20 transmitter means comprising a microphone support extending forward from the earpiece assembly at one side of the head of a person wearing the headset to a position generally adjacent the mouth of the person, a microphone at the forward end of the microphone support for picking up
25 sounds from the person, and electrical conductor means for connecting the microphone to a microphone mechanism associated with the transmitter of the telephone.

24. A headset as set forth in claim 23 further comprising a quick-connect, quick-disconnect coupling for releasably coupling said electrical conductor means to said microphone mechanism associated with the transmitter of the
5 telephone.

25. A headset as set forth in claim 23 wherein said earpiece assembly comprises a housing and an ear insert attached to the housing adapted to be positioned in or near the outer opening of an ear of a person when the earpiece
5 assembly is mounted on the head, the upper end of said acoustical receiving tube being connected to the housing and communicating acoustically with the ear insert for transmission of sound to the ear, and wherein said microphone support comprises a tubular arm having a rearward
10 end connected to said housing, said electrical conductor

means extending rearwardly from said microphone through said tubular arm and through said housing for connection to said microphone mechanism.

26. A headset for a cellular telephone, said cellular telephone having a speaker and a transmitter, said headset comprising:

5 an acoustical earpiece assembly comprising an earpiece housing and an ear insert attached to the housing adapted to be positioned in or near the outer opening of the ear when the headset is worn,

a hanger on the housing engageable with the ear for supporting the earpiece assembly on the ear,

10 a flexible acoustical receiving tube having an upper end connected to said earpiece housing and acoustically communicating with said acoustical chamber, and a lower end adapted for acoustical communication with the telephone speaker for receiving sound emitting from the speaker,

15 transmitter means attached to the earpiece assembly for picking up sounds made by a person wearing the headset, and for transmitting such sounds to the transmitter of the telephone,

20 said transmitter means comprising a relatively short acoustical pick-up tube extending forward from said earpiece housing at one side of the head of a person wearing the headset, and a flexible acoustical transmitting tube having an upper end connected to said earpiece housing and
25 communicating acoustically with said pick-up tube, and a lower end adapted to communicate acoustically with the transmitter of the telephone, said acoustical pick-up and transmitting tubes being adapted to acoustically transmit

sounds made by a person wearing the headset to the
30 transmitter of the telephone,
said housing being pivotable relative to said
hanger about an axis extending in generally side-to-side
direction with respect to the head of a person wearing the
headset to enable adjustment of the position of said
35 acoustical pick-up tube relative to the head of said person.

27. A headset as set forth in claim 26 further
comprising a detent mechanism for maintaining said housing
in a selected position of angular adjustment.


28. A headset as set forth in claim 27 wherein
said acoustical pick-up tube is generally J-shaped, having a
shank portion extending forward from the housing at one side
of the head of a person wearing the headset, and a forward
5 end portion extending generally laterally with respect to
the shank portion, the shank portion of the pick-up tube
having a connection with the housing permitting rotation of
the pick-up tube about a longitudinal axis of the shank
portion thereby to permit adjustment of the position of the
10 forward end portion of the pick-up tube relative to the
mouth of a person wearing the headset.

29. A headset as set forth in claim 28 wherein
said earpiece assembly further comprising a connector
connecting the shank portion of the pick-up tube to the
housing, said housing comprising two separate parts adapted
5 to fasten together to form a unitary housing, said housing
being configured to hold said connector rotatably captive
with respect to the housing when the two parts of the
housing are fastened together.


30. A headset as set forth in claim 29 wherein said acoustical receiving and transmitting tubes are integrally connected in side-by-side relation.

1 / 6.

FIG. 1



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)

FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



6 / 6

FIG. 13





FIG. 14



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/06614

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : H04M 1/05
US CL : 455/89,90; 379/430

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 455/89,90, 344, 345, 350, 351; 379/430, 431, 432, 433; 381/154

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
NONE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	TELECONNECT MAGAZINE, issued March 1991, see the figures in the Cellular Headset section, see page 119.	1-30
Y	US, A, 4,090,042 (LARKIN) 16 MAY 1978, see figures 1-5, see column 1, lines 42-67.	3-18, 23-26, and 28-30
Y	US, A, 3,830,334 (COSTA) 20 AUGUST 1974, see figure 2, see column 2, lines 36-52.	1, 23 and 26
Y	US, A, 5,212,734 (TSAO) 18 MAY 1993, see figure 2.	2 and 19-20

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be part of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 31 AUGUST 1995	Date of mailing of the international search report 25 SEP 1995
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231	Authorized officer <i>Thanh Le</i> THANH LE
Facsimile No. (703) 305-3230	Telephone No. (703) 305-4700